


**EVT125**

ADOGF030VAS0025E03

Connection technology



**Product characteristics**

Socket

For sensors with

M8 connector

Free from silicone

gold-plated contacts

For hygienic and wet areas in the food industry

**Electrical data**

Electrical design		AC/DC
Operating voltage	[V]	50 AC / 60 DC
Current rating	[A]	3
Protection class		III

**Environment**

Ambient temperature	[°C]	-25...80, cULus: max. 50 °C
Ambient temperature (moving)	[°C]	5...80, cULus: max. 50 °C
Protection		IP 65 / IP 67 / IP 68 / IP 69K

**Mechanical data**

Design		straight
Material body		housing: PVC orange; sealing: EPDM
Material nut		stainless steel 316L / 1.4404
Tightening torque for knurled nut [Nm]		0.3...0.5
Drag chain suitability		Bending radius for flexible applications: min. 10 x cable diameter max. 3.3 m/s for a horizontal travel length of 5 m and max. acceleration of 5 m/s <sup>2</sup> Travel speed: > 1 million Bending cycles: > 1 million Torsional strain: ± 180 °/m
Weight	[kg]	0.814

**Electrical connection**

Connection		PVC cable / 25 m; 3 x 0.34 mm <sup>2</sup> (42 x Ø 0.1 mm); Ø 4.9 mm
Sheath color		orange

**Wiring**





## EVT125

ADOGF030VAS0025E03

Connection technology

Core colors  
BK black  
BN brown  
BU blue



### Remarks

Pack quantity [piece] 1